




TEST REPORT

According to ANSI/IES LM-80-15
For

Hongli Zhihui Group Co.,Ltd. Guangzhou Branch
Room 316, Building 2, No.1, Xianke Yi Road, Huadong Town, Huadu District, Guangzhou, China

Model: HL-A-3014H416W-S1-08HL-HR6

Report Type: 6000 Hours Test Report	Product Type: LED Package
Reviewed By: Pote Wang	<i>Pote Wang</i>
Report Number:	SZ2220725-33705E-EE-6000
Test Date:	2022-07-29 to 2023-04-05
Report Date:	2023-05-06
Approved by:	Blake Zhang / EE Engineer <i>Blake Zhang</i>
Prepared By:	Bay Area Compliance Laboratory Corp. (Shenzhen) 5/F(B-We1) -7/F, The 3rd Phase of Wan Li Industrial Building D, Shihua Road, Foshan Free Trade Zone Shenzhen, Guangdong, China. Tel: +86-755-33320018 Fax: +86-755-33320008
Test Facility:	Test facility is located at No.12, Pinglong East 1st Road, Tangxia Town, Dongguan, Guangdong, China.



Note: This test report is prepared for the customer's use only and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratory Corp. (Shenzhen). This report may not be used to claim product certification, approval, or endorsement by NVLAP, or an agency of the U.S. Government.



TABLE OF CONTENTS

1 - General Information	3
1.1 Description of LED Light Sources [#]	3
1.2 Standards and Reference Documentations.....	3
1.3 Testing Equipment.....	4
1.4 Drive Level.....	4
1.5 Ambient Conditions for Maintenance Test.....	4
1.6 Photometric Measurement Method and Uncertainty.....	4
1.7 Statement of Traceability.....	4
1.8 Sample Set.....	5
2 - Summary of Test Result	6
3 - Test Data	7
3.1 Data Set 1, 55°C, 30mA (Lumen Maintenance).....	7
3.2 Data Set 1, 55°C, 30mA (Forward Voltage).....	8
3.3 Data Set 1, 55°C, 30mA (Chromaticity Shift).....	9
3.4 Data Set 2, 85°C, 30mA (Lumen Maintenance).....	10
3.5 Data Set 2, 85°C, 30mA (Forward Voltage).....	11
3.6 Data Set 2, 85°C, 30mA (Chromaticity Shift).....	12
4 - DUT Photo	13
4.1 Mechanical Dimensions.....	13
4.2 DUT Photo.....	13
Directions	14



Bay Area Compliance Laboratories Corp. (Shenzhen)

5/F(B-We1) -7/F, 1st Phase of Wan Li Industrial
Building D, Shihua Road, Foshan Free Trade Zone Shenzhen, Guangdong, China.
The NVLAP Lab Code is 200707-0

1 - General Information

1.1 Description of LED Light Sources[#]

Sample Size:

50 PCS test samples were in good condition and received on 2022-07-25. The samples were numbered from 1 to 25 and 26 to 50.

Manufacturer: Hongli Zhihui Group Co.,Ltd. Guangzhou Branch



- *ENERGY STAR Requirements for the Use of LM-80 Data (This standard was not accredited by NVLAP)

1.3 Testing Equipment

Device	Manufacture	Model No	Serial No	Calibration date	Calibration due date
0.5m integrating sphere	EVERFINE	AIS-2	G185304TA1381172	2022-11-18	2023-11-17
LED Test Source	EVERFINE	LTS-300	P185616CD1371113	2022-11-18	2023-11-17
High Accuracy Array Spectroradiometer	EVERFINE	HAAS-2000	P600674CM1381123	2022-06-07	2023-06-06
Standard Light Source	EVERFINE	D062	1011093	2021-10-15	2023-10-14
Multilayer aging machine	BACL	B2-270	20015	2022-10-19	2023-10-18
Program-controlled D.C. Stabilized Voltage Supply	Hanshenpuyuan	HSPY-60-03	N/A	2022-11-18	2023-11-17

1.4 Drive Level

Samples are driven with a constant direct current (DC) during maintenance test, photometric and electrical measurement. The current value was regulated to within $\pm 3\%$ of the specified value of the manufacturer during maintenance test, and was within $\pm 0.5\%$ during photometric and electrical measurement test.

1.5 Ambient Conditions for Maintenance Test

For lumen maintenance test, samples within one data set, were installed on cooling boards in thermal chambers with minimal ambient airflow. The case temperature and ambient temperature was monitored by thermocouples which one was soldered to the coldest DUTs' case (TMP_{LED}) location, while the other is mounted at a distance of 5 mm above the TMP location.

During life testing, TMP_{LED} of the coldest LEDs were maintained at a temperature that was greater than or equal to $2^{\circ}C$ below the corresponding nominal case temperature. Surrounding air was maintained at a temperature that was greater than or equal to $5^{\circ}C$ below the corresponding nominal case temperature. Thermocouples were shielded from direct DUT optical radiation and comply with ASTM E230 Table 1 "Special Limits".

Samples were connected to DC power supply in series circuits with a constant current. The forward current was regulated to within $\pm 3\%$ of the specified value of the manufacturer.

The relative humidity within chamber was kept less than 65% during test.

For photometry measurement, the ambient temperature during test was set to $25^{\circ}C \pm 2^{\circ}C$, RH <65%.

1.6 Photometric Measurement Method and Uncertainty

Integrating sphere and spectroradiometer is used to measure luminous flux and chromaticity coordinate $u'v'$. 2π measurement was used and sample was driven by DC power supply. The forward current was regulated to within $\pm 0.5\%$ of the nominal value. The test system was calibrated by halogen reference lamp. The ambient temperature during test was set to $25^{\circ}C \pm 2^{\circ}C$, RH <65%. The temperature measurement point was located in the sphere and the temperature was detected by a temperature probe.

The uncertainty of the light output measurements is $U=1.59\%$ ($K=2$), at the 95% confidence level. The uncertainty of the correlated color temperature measurements is $U=21K$ ($K=2$), at the 95% confidence level.

The uncertainty of the temperature is $U=0.8671^{\circ}C$ ($K=2$), at the 95% confidence level.

1.7 Statement of Traceability

Bay Area Compliance Laboratories Corp. (Shenzhen) attested that all calibration has been performed using suitable standards traceable to National Primary Standards and International System of Units (SI).



Bay Area Compliance Laboratories Corp. (Shenzhen)

5/F(B-Weil)-7/F, 1st Phase of Wan Li Industrial
Building D, Shihua Road, Futian Free Trade Zone Shenzhen, Guangdong, China.
The NVLAP Lab Code is 200707-0

1.8 Sample Set

Data Set 1: 55°C, 30mA



2 - Summary of Test Result

Data Set:	Sample Size	Failures Observed:	Test Interval	Test Duration	α	β	Reported TM-21 L ₇₀ Lifetime
1	25	0	1000hrs	6000hrs	1.981E-06	1.004	>36000 hours
2	25	0	1000hrs	6000hrs	2.111E-06	1.004	>36000 hours


Average Lumen Maintenance (Percentage of Initial Luminous Flux)

Data Set:	1000hrs	2000hrs	3000hrs	4000hrs	5000hrs	6000hrs
1	100.18%	99.97%	99.76%	99.57%	99.38%	99.19%
2	100.14%	99.95%	99.76%	99.54%	99.32%	99.09%

Average Chromaticity Shift

Data Set:	1000hrs	2000hrs	3000hrs	4000hrs	5000hrs	6000hrs
1	0.0001	0.0002	0.0003	0.0005	0.0007	0.0009
2	0.0001	0.0002	0.0004	0.0006	0.0008	0.0010

Average Lumen Maintenance and Chromaticity Shift VS. Time



Bay Area Compliance Laboratories Corp. (Shenzhen)
5/F(B-We1) -7/F, 1he 3rd Phase of Wan Li Industrial



Bay Area Compliance Laboratories Corp. (Shenzhen)

5/F(B-Weil) -7/F, 1st 3rd Phase of Wan Li Industrial
 Building D, Shihua Road, Futian Free Trade Zone Shenzhen, Guangdong, China.
 The NVLAP Lab Code is 200707-0

3.2 Data Set 1, 55°C, 30mA (Forward Voltage)

No.	Forward Voltage (V)						
	0hr(Initial)	1000hrs	2000hrs	3000hrs	4000hrs	5000hrs	6000hrs
1	2.913	2.919	2.915	2.916	2.919	2.906	2.914
2	2.919	2.915	2.922	2.918	2.900	2.923	2.900
3	2.916	2.934	2.919	2.917	2.907	2.914	2.916
4	2.913	2.911	2.914	2.901	2.916	2.906	2.914
5	2.909	2.919	2.909	2.902	2.927	2.908	2.912
6	2.904	2.913	2.905	2.902	2.900	2.929	2.902
7	2.906	2.924	2.907	2.916	2.913	2.925	2.913
8	2.909	2.916	2.909	2.908	2.906	2.919	2.911
9	2.906	2.917	2.907	2.904	2.900	2.918	2.910
10	2.910	2.914	2.912	2.916	2.918	2.919	2.912
11	2.905	2.909	2.906	2.904	2.917	2.909	2.919
12	2.919	2.918	2.921	2.905	2.908	2.903	2.919
13	2.906	2.921	2.909	2.915	2.900	2.900	2.918
14	2.912	2.922	2.915	2.911	2.901	2.918	



Bay Area Compliance Laboratories Corp. (Shenzhen)

5/F(B-Weil) -7/F, 1st Phase of Wan Li Industrial Building D, Shihua Road, Foshan Free Trade Zone Shenzhen, Guangdong, China.
The NVLAP Lab Code is 200707-0

3.3 Data Set 1, 55°C, 30mA (Chromaticity Shift)

No.	u'	v'	CCT(K)	Chromaticity Shift ($\Delta u'v'$)					
	0hr(Initial)			1000hrs	2000hrs	3000hrs	4000hrs	5000hrs	6000hrs
1	0.2591	0.5334	2745	0.0001	0.0002	0.0004	0.0005	0.0007	0.0009
2	0.2567	0.5292	2816	0.0001	0.0002	0.0004	0.0005	0.0008	0.0009
3	0.2585	0.5309	2768	0.0001	0.0002	0.0003	0.0005	0.0007	0.0008
4	0.2586								



Bay Area Compliance Laboratories Corp. (Shenzhen)

5/F(B-Weil) -7/F, 1st 3rd Phase of Wan Li Industrial
 Building D, Shihua Road, Futian Free Trade Zone Shenzhen, Guangdong, China.
 The NVLAP Lab Code is 200707-0

3.4 Data Set 2, 85°C, 30mA (Lumen Maintenance)

No.	Φ(lm)	Lumen Maintenance (%)					
	0hr(Initial)	1000hrs	2000hrs	3000hrs	4000hrs	5000hrs	6000hrs
26	9.525	100.25	100.08	99.93	99.64	99.41	99.20
27	9.764	100.18	99.97	99.76	99.59	99.37	99.18
28	9.743	100.10	99.78	99.60	99.24	99.07	98.80
29	9.729	99.95	99.87	99.72	99.48	99.23	98.94
30	9.678	100.25	99.98	99.60	99.26	99.06	98.82
31	9.686	100.27	100.03	99.86	99.74	99.64	99.45
32	9.724	100.10	99.77	99.59	99.30	99.16	98.97
33	9.605	99.96	99.86	99.74	99.70	99.43	99.30
34	9.558	99.96	99.90	99.82	99.67	99.48	99.15
35	9.705	100.33	100.06	99.79	99.42	99.17	98.90
36	9.535	100.21	100.02	99.66	99.42	99.26	99.02
37	9.792	100.12	100.06	99.87	99.72	99.41	99.26
38	9.795	100.29	100.02	99.64	99.51	99.13	98.89
39	9.611	100.24	100.03	99.76	99.40	99.02	98.92
40	9.636	100.22	99.91	99.64	99.46	99.28	99.06
41	9.503	100.29	99.98	99.74	99.64	99.40	99.06
42	9.899	100.17	99.87	99.75	99.40	99.28	99.02
43	9.690	100.10	99.92	99.81	99.68	99.57	99.25
44	9.669	100.09	100.01	99.74	99.56	99.31	99.14
45	9.570	100.07	100.03	99.94	99.79	99.54	99.40
46	9.611	99.89	99.76	99.69	99.57	99.51	99.21
47	9.693	100.11	100.04	99.88	99.63	99.38	99.08
48	9.753	100.02	99.97	99.76	99.59	99.26	99.11
49	9.511	99.93	99.98	99.86	99.50	99.23	98.90
50	9.599	100.27	99.96	99.77	99.60	99.39	99.08
Avg.	9.663	100.14	99.95	99.76	99.54	99.32	99.09
Med.	9.678	100.12	99.98	99.76	99.57	99.31	99.08
st dev	0.101	0.13	0.09	0.10	0.15	0.16	0.17
Min.	9.503	99.89	99.76	99.59	99.24	99.02	98.80
Max.	9.899	100.33	100.08	99.94	99.79	99.64	99.45



Bay Area Compliance Laboratories Corp. (Shenzhen)

5/F(B-Weil) -7/F, 1st 3rd Phase of Wan Li Industrial
 Building D, Shihua Road, Futian Free Trade Zone Shenzhen, Guangdong, China.
 The NVLAP Lab Code is 200707-0

3.5 Data Set 2, 85°C, 30mA (Forward Voltage)

No.	Forward Voltage (V)						
	0hr(Initial)	1000hrs	2000hrs	3000hrs	4000hrs	5000hrs	6000hrs
26	2.910	2.919	2.913	2.902	2.914	2.919	2.903
27	2.916	2.929	2.921	2.916	2.917	2.917	2.912
28	2.915	2.915	2.919	2.931	2.915	2.919	2.936
29	2.912	2.928	2.917	2.918	2.914	2.911	2.928
30	2.905	2.915	2.908	2.917	2.910	2.905	2.917
31	2.907	2.919	2.912	2.901	2.916	2.917	2.912
32	2.919	2.924	2.924	2.915	2.920	2.930	2.914
33	2.913	2.917	2.916	2.910	2.915	2.913	2.916
34	2.906	2.910	2.910	2.911	2.909	2.904	2.904
35	2.934	2.940	2.939	2.927	2.910	2.902	2.914
36	2.912	2.923	2.916	2.919	2.921	2.914	2.912
37	2.933	2.938	2.937	2.929	2.906	2.927	2.900
38	2.933	2.936	2.937	2.914	2.919	2.921	2.918
39	2.910	2.914	2.914	2.907	2.908	2.914	2.918
40	2.916	2.920	2.920	2.926	2.918	2.921	2.919
41	2.913	2.917	2.919	2.932	2.904	2.911	2.918
42	2.922	2.921	2.921	2.910	2.912	2.913	2.917
43	2.920	2.919	2.920	2.917	2.901	2.918	2.907
44	2.909	2.912	2.910	2.918	2.913	2.910	2.931
45	2.922	2.924	2.924	2.922	2.926	2.925	2.919
46	2.922	2.923	2.923	2.924	2.922	2.915	2.926
47	2.916	2.917	2.919	2.906	2.919	2.919	2.937
48	2.919	2.917	2.919	2.916	2.907	2.912	2.917
49	2.912	2.912	2.913	2.919	2.906	2.930	2.914
50	2.918	2.919	2.921	2.930	2.908	2.928	2.919
Avg.	2.917	2.921	2.920	2.917	2.913	2.917	2.917
Med.	2.916	2.919	2.919	2.917	2.914	2.917	2.917
st dev	0.008	0.008	0.008	0.009	0.006	0.008	0.009
Min.	2.905	2.910	2.908	2.901	2.901	2.902	2.900
Max.	2.934	2.940	2.939	2.932	2.926	2.930	2.937



Bay Area Compliance Laboratories Corp. (Shenzhen)

5/F(B-We1) -7/F, 1he 3rd Phase of Wan Li Industrial
Building D, Shihua Road, Fuzhou Free Trade Zone Shenzhen, Guangdong, China.
The NVLAP Lab Code is 200707-0

Bay Area Compliance Laboratories Corp. (Shenzhen)